

RSG Timber & Paslode joint approval for fixing RSG Yellow BS Batten with Paslode 360Xi nailer and roof batten nail

RSG Yellow® BS Battens - Quality, Compliance and Sustainability

RSG Timber is an independent privately owned specialist roofing batten importer with staff having over 30 years' experience specifically in roofing battens. Their primary focus is to specialise in the supply and distribution of correctly graded British Standard roofing battens throughout the UK.

RSG Yellow BS battens are a high grade quality BS batten manufactured from slow grown kiln dried side boards at their sawmill partner in the Baltics who have invested over 3 Million Euros in brand new state of the art batten production lines. The battens are then shipped to the UK and distributed from their two timber terminals with a speedy delivery service.

Benefits of RSG Yellow BS Batten

All RSG Yellow® BS battens are correctly graded and compliant with BS 5534, supported by independent third-party accreditation through CATG/BMC and are CCPI assessed - placing RSG Yellow® BS Battens among only three batten producers in the UK to achieve this robust standard.

- Correctly graded to BS 5534:2014+A2:2018
- CCPI assessed 015500183/1027
- Full Chain of Custody either FSC or PEFC certified
- 3rd party quality assurance accreditation by CATG/BMC
- Pressure treated correctly to BS 8417 to use Class 2 with Wood Protection Association Benchmark approved treatment to give a 60 year service life against insect attack and wood rotting fungi when installed correctly
- Kiln dried side boards are used to ensure stability and industry conformity.
- Each piece is full to size and correctly stamped showing supplier, grade, size, 3rd party assurance and origin/species.



Paslode 360Xi Complete System

Tool Code: 019700



Nail Fuel Pack: 141073, 141089 "Handy Pack"



Paslode Roof Batten Nail. 63 x 3.1mm Ring Shank Galv-Plus Nail

- Industry approved BS 5534
- Roof batten nail
- Eurocode 5 Compliant
- Service Class 2 Compliant

BENEFITS

- The perfect tool and nail system for nailing 25mm BS 5534 approved batten, for a high-quality finish.
- Saves time and is safer when compared to traditional hand nailing.
- Can be fixed using our BS 5534 and industry-approved Paslode 63 x 3.1mm Ring Shank Galv-Plus roof batten nail.
- Drastically reduces fatigue on arms, back and shoulders – light weight and perfectly balanced offering productive working all day long.
- A high performance lithium battery offers up to 13,000 shots per single charge (or around 5 boxes of 2200 Paslode nails).
- Paslode all-weather fuel cells allows you to work in extreme cold or hot weather conditions.
- **Easy to use rotating depth of drive adjuster** - allows optimal embedment of nails for a clean flush finish.
- **New aggressive nose probe** – offers extreme "grab" onto the timber batten.
- **Paslode System training** — industry recognised certificates offered when using our system.

Grading

Not all roofing battens are created equal. Under BS 5534, every batten used in a tiled or slated roof must be fully graded for structural use. That grading ensures battens can safely support the loads placed on them during installation and throughout the life of the roof. RSG Yellow® BS Battens are machine graded and produced in line with the standards the UK roofing industry relies on every day because when it comes to roofing, the structure beneath the tiles matters just as much as the tiles themselves.

RSG Timber only uses slow grown kiln dried side boards ensuring a high level of consistent quality. Battens are machined and graded by brand new state of the art sawmill facilities with laser accuracy and each piece is stamped ready for packaging and treatment.

The grading process controls the following:

- Battens are full to size
- Wane
- Knots comply
- Splits and fissures
- Slope of Grain
- Rate of Growth
- Decay and insect attack
- Resin pocket size



Compliance & Certification

RSG Yellow® BS Battens are fully graded to BS 5534, have 3rd party quality assurance backed by CATG/BMC and are CCPI assessed meeting all industry standards. Please see their website for full details.

Treatment

A fully computerised packaging system ensures complete traceability and consistency, with uniform, tightly banded packs ready for treatment. Battens are pressure treated in line with BS 8417 and meet Wood Protection Association Benchmark industry standards.

Roofing battens operate in one of the toughest environments in construction. They sit within a roof structure where moisture, ventilation and temperature changes are constant factors. That's why treatment standards are critical. Proper timber treatment helps protect battens against fungal decay and extends the life of the roof structure. RSG Yellow® BS battens are all treated in line with recognised industry standards to ensure long-term performance.


Sustainability & Traceability

RSG Timber is passionate about sustainability and only uses raw material from sustainable forestry sources for their BS Battens which have full Chain of Custody either FSC or PEFC. Traceability sits at the heart of the RSG Yellow® BS Batten supply chain because confidence in materials starts with knowing exactly what you're installing.

Version 1.1 June 2026



**RSG YELLOW®
BS BATTEN**



**NEW P-HEAD &
FULL ROUNDRIIVE
HEADS FOR ALL
PASLODE ROOF
BATTEN NAILS.**




- **Full Roundrive heads** - for improved Pull-through capacity.
- **P-head** – for in situ product identity.
- **P-head** – a visual aid to encourage nail head fixed flush to batten surface.

ROOFING NAILS



**SCAN ME
TO LEARN MORE**

FIND OUT MORE



First Floor, Unit 8 St Georges Court,
Kirkham Lancashire PR4 2EF

Contact Details:
Tel: 01772 954500
Email: sales@rsgtimber.co.uk



Follow RSG Timber Limited



1 Wheatstone Place, Southfield Industrial Estate
Glenrothes, Fife KY6 2SW

Customer Services: 0800 833381
paslode.co.uk



Follow us @PaslodeUK